



Atlas Instantaneous Gas Water Heater

Saving you Money when Used In:

Normal Domestic houses, Townhouses, Duplex flats, Laundries, Workshops, Factories, Holiday Resorts, Caravan Parks, Game Farms, Guest Houses, Hotels, Low cost Housing units, Service Stations, Farms & Doctors rooms.

Specification & Features:

- SABS Compliant and tested to SANS 1539:2005
- Appliance verification permits available on all sizes from: The Liquified Petroleum Gas Safety Association of SA (LPGSASA).
- Automatic operation without pilot light, the LPG Gas burner ignites upon opening the hot water tap providing instant hot water, closing the tap will immediately cut off the gas supply and extinguish the flame.
- Full safety protection if the flame in the water heater is unexpectedly extinguished the pulse igniter will immediately re-light the flame.
- An overheating protection device automatically cuts off the gas in the event of overheating.
- Automatic Pulse Ignition from two D size alkaline batteries.
- May be installed Indoors as they are rated Type "B" from SANS 1539.
- Rated for water pressure of 2.8kpa with water flow regulator to protect against pressure surges with by pass shunt valve should the pressure exceed rating.
- Fittings for standard 8mm approved gas hosing.



Atlas Gas Geyser

Instant and neverending Economical Hot Water Supply

Recommended Geyser Sizing:

To size a gas geyser for efficient use, one needs to determine whether the heater's capacity is going to be fully utilized every time it is switched on.

E.g. if the requirement is a 16lt for the whole household and a 16lt installed, then every time a hot water tap is opened 3.06kg/hr gas will be burned, therefore it would be more economical to install both a 10lt & a 6lt side by side running off the same gas bottle to serve different heating disciplines.

Flow rate: Application

lt/min

6lt: Small Kitchen or Basin & Camping

8lt: Kitchen & Shower

10lt: Laundry, Shower+ Basin

12lt: Laundry, Shower+ Basin with Low water pressure

16lt: Household supply

Average gas usage

Geyser Size	Kg per hour
6	1.11
8	1.49
10	1.93
12	2.29
16	3.06
20	3.82

Price Excl VAT ex works Gauteng and Product Detail

Product Code	Price	Dimensions	Weight kg
AT-OM 6lt	R861.00	570x325x205	5.2
AT-OM 8lt	R1250.00	660x390x250	7.9
AT-OM 10lt	R1435.00	720x400x240	10.29
AT-OM 12lt	R1573.25	720x390x250	9.5
AT-OM 16lt	R2140.00	830x436x263	19
AT-OM 20lt	R2795.00		



Inline & Manual changeover Regulator



Bullnose Regulator & Flexible Flue

For peace of mind let Omnilite arrange an Installation with selected and Registered LPGSA Gas technician to ensure safe, correct operation to comply Legally and to Qualify for the one year Warranty.